

AQUAMAT TR

-
- **SUMMARY** **WATER BASE FINISH FOR MATTING THERMOPLASTIC (TR) SOLES WITHOUT CHLORINATION**
-
- **CHARACTERISTICS** **AQUAMAT TR** is a water base finish for special mat effects. It gives a mat, equalizing effect with a soft touch onto thermoplastic rubber surfaces, not treated with chlorinated primers.
AQUAMAT TR is an all-purpose water base mat finish used on TR rubber. The special formulation allows finishing all synthetic TR materials by direct application of **AQUAMAT TR** on to the material.
- **APPLICATION**
 - **AQUAMAT TR** is applied by manual spraying or with suitable equipment, directly onto the soles or heels
 - **AQUAMAT TR** is applied by spray-gun (pressure 4.5 - 6 atm, 1.2 nozzle), either manually or by machine.
The product must be nebulised very well (if the application of **AQUAMAT TR** is it too wet or abundant, matt effect is not uniform)
 - let it dry completely (at least 20 - 30 minutes) eventually use a drying oven at 40 - 70°C
 - this product peculiarity is the excellent spraying. It can be applied also or the special spraying machines produced by “MET “ in Gropello Cairoli or manually by a spraying gun - nozzle diameter 1.2 at a pressure of 5-6 atm. We suggest to well stir the product before use
 - so to obtain a uniform final effect, we recommend to keep the product constantly under agitation
- **COLOURS** 32200 Colorless
- **SOLVENTS** Use **WATER** for washings

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

02-10-2023 GA/pm



QUALITY MANAGEMENT
SYSTEM
CERTIFIED ISO 9001

TECHNICAL DATA SHEET

Series

22

AQUAMAT TR

● *SUMMARY*

**WATER BASE FINISH FOR MATTING THERMOPLASTIC (TR) SOLES
WITHOUT CHLORINATION**

● *STORAGE*

The expire date of the product shown on the label is valid for products if kept away from direct heat and cold and at standard storage conditions (minimum temperature 4°C to maximum 40°C).
Exceeding the expiration date does not necessarily mean that the product no longer meets the specifications or values set.
However, before using this product after the expiration date, Kenda Farben recommends checking whether it still meets the reference specifications or values. Kenda Farben will not be in any way responsible for failure to comply with specifications or values set after the deadline or due to incorrect storage that can shorten the life of the product.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

02-10-2023 GA/pm