



TECHNICAL DATA SHEET

ECOSAR 1-66-B

● SUMMARY

SYNTHETIC LATEX ADHESIVE IN AQUEOUS DISPERSION

● USE

Specifically suitable for the footwear industry for natural and synthetic material coupling. While for coupling natural material it's applied by spraying system, for the synthetics it has to be combined with the catalyst "KENDOR ECO A" by means of a special spraying machine.

● CHARACTERISTICS

– Colour	ivory white liquid
– Viscosity	20 - 100 cps
– pH value	between 11 and 14
– Open time	2 / 3 minutes

● APPLICATION

- Use the product by spraying, brushing and rolling

Notes: it is suggested to use the adhesive at temperatures not lower than 18°; in case the material is stocked in cold ambients, recondition before using

● STORAGE

The expire date of the product shown on the label is valid for products if kept away from direct heat and cold and at standard storage conditions (minimum temperature 4°C to maximum 40°C).
Exceeding the expiration date does not necessarily mean that the product no longer meets the specifications or values set.
However, before using this product after the expiration date, Kenda Farben recommends checking whether it still meets the reference specifications or values. Kenda Farben will not be in any way responsible for failure to comply with specifications or values set after the deadline or due to incorrect storage that can shorten the life of the product.

● NOTE

Stir it well before its use. Keep from freezing.
Keep the packings perfectly closed.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

11-12-2024 GA/pm