



## TECHNICAL DATA SHEET

# ECOSAR 40

### ● SUMMARY

### WATER BASE ADHESIVE AT SYNTHETIC LATEX BASE

### ● USE

Particularly suitable for bonding of natural materials (leather), especially if poorly absorbent, with strong grip and tear resistance. It can be applied by spraying-gun, roll-machine and brush.

### ● CHARACTERISTICS

- |                                 |                      |
|---------------------------------|----------------------|
| – Appearance                    | white ivory liquid   |
| – Viscosity: (Brook, RVT, 20°C) | 30/50 cps (G2 – V20) |
| – pH value                      | between 8 and 9      |
| – Solid content                 | 54 +/- 3             |

### ● APPLICATION

- Use the product as follows:
  - room temperature of adhesive and materials to be bond: approx. 20-22°C
  - humidity of materials to be bond: 8-10%
  - relative air humidity: 65-75%
- **ECOSAR 40** has to be applied on both side of bonding material
- let dry at least for 7/30 minutes and then press
- during spraying process it is necessary to adjust the distance of the spraying-gun in order to obtain an homogeneous spraying
- open time 30'

**Notes:** it is suggested to use the adhesive at temperatures not lower than 18°; If the adhesive is stored in a cold room, it has to be reconditioned before use

### ● STORAGE

The expire date of the product shown on the label is valid for products if kept away from direct heat and cold and at standard storage conditions (minimum temperature 4°C to maximum 40°C).  
Exceeding the expiration date does not necessarily mean that the product no longer meets the specifications or values set.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

17-07-2023 GA/pm



QUALITY MANAGEMENT  
SYSTEM  
CERTIFIED ISO 9001

## TECHNICAL DATA SHEET

---

# ECOSAR 40

---

### ● SUMMARY

### WATER BASE ADHESIVE AT SYNTHETIC LATEX BASE

---

However, before using this product after the expiration date, Kenda Farben recommends checking whether it still meets the reference specifications or values. Kenda Farben will not be in any way responsible for failure to comply with specifications or values set after the deadline or due to incorrect storage that can shorten the life of the product.

### ● NOTE

Stir it well before its use. Keep from freezing.  
Keep the packings perfectly closed.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

17-07-2023 GA/pm